Evidence of Performance

Air permeability, Watertightness, Resistance to wind load

Test Report No. 15-002227-PR02 (PB-A01-02-en-01)

Client	KURTOGLU ALUMINYUM BAKIR KURSUN SAN. A.S. Haciseremet Mevkii TEM Corlu Cikisi Velimese 59860 Tekirdag Turkey
Product	Single tilt and turn window with fixed sublight
Designation	System designation: 74T
Performance-relevant product details	Material: Aluminium profiles with thermal break
Overall dimensions (W x H)	792 mm x 2,000 mm
Special features	-/-

Results

Air permeability according to EN 12207:1999-11



Class 4

Watertightness according to EN 12208:1999-11



Class 9A

Resistance to wind load according to EN 12210:1999-11/AC:2002-08



Class C3 / B3

ift Rosenheim 26.08.2015


Andreas

Andreas Graf Deputy Head of Testing Department Construction Product Testing



Michael Breckl-Stock, M.Eng., Dipl.-Ing. (FH) Operating Testing Officer Construction Product Testing





ift Rosenheim GmbH Theodor-Gietl-Str. 7-9 D-83026 Rosenheim

Kontakt Tel. +49.8031.261-0 Fax +49.8031.261-290 www.ift-rosenheim.de

Prüfung und Kalibrierung – EN ISO/IEC 17025 Inspektion – EN ISO/IEC 17020 Zertifizierung Produkte – EN ISO/IEC 17065 Zertifizierung Managementsysteme – EN ISO/IEC 17021





EN 14351-1:2006+A1:2010

Test standard/s: EN 1026:2000-06 EN 1027:2000-06 EN 12211:2000-06

Basis

Correspond/s to the national standard/s (e.g. DIN EN)

Representation



Instructions for use

The manufacturer is allowed to use the results obtained for preparing a Declaration of Performance in accordance with the Construction Products Regulation 305/2011/EC. Observe the specifications set out by the applicable product standard.

Validity

The data and results refer solely to the tested and described specimen. Classification remains valid as long as the product and the above basis remain unchanged. The results can be extrapolated under the manufacturer's own liability subject to observance of the relevant specifications set out by the applicable product standard. This test/evaluation does not allow any statement to be made on any further characteristics regarding performance and quality of the construction presented; in particular the effects of weathering and ageing were not taken into account.

Notes on publication

The ift-Guidance Sheet "Advertising with ift test documents" applies. The cover sheet can be used as an abstract.

The report contains a total of 22 pages.

